


Gap Subs Manufacturing and Service

PDT manufactures high quality DOUBLE and SINGLE gap subs for EM transmission tools.

WE OFFER THE FOLLOWING:

- Gap Subs Manufacturing from OD – 3.5” - 9.5”
- Gap Subs Service and Maintenance of Most Brands
- Proprietary Gap Subs Thread Coating Technology
- In-House Break out Machine With Torque Graph Print Outs and PDF
- Durable Long Lasting 3 Stage Gap Isolation Protection
- Fast Recoat/Rebuild Turnaround Times
- Industry High MTBF on PDT Brand Gap Sub Design.
- Multi-tool Platform Compatibility

PDT Gap Sub Specifications				
Sub O.D.	3-3/4”	4”	4-3/4”	6-1/2”
Sub I.D.	2.25”	2.25”	2.69”	2.81”
Length Face to Face	40”	40”	40”	40”
Threads	2-7/8” SLH-90 Pin by Box or Client Selects	2-7/8” SLH-90 Pin by Box or Client Selects	3-1/2” IF Pin by Box or Client Selects	4-1/2” XH Pin by Box or Client Selects
Max Downhole Pressure	25,000 psi	25,000 psi	25,000 psi	25,000 psi
Torque Specifications	4000 lbs/ft	4000 lbs/ft	10000 lbs/ft	18000 lbs/ft
Max Dogleg Severity (Rotating)	20° / 100 ft	15° / 100 ft	12° / 100 ft	10° / 100 ft
Max Dogleg Severity (Sliding)	50° / 100 ft	50° / 100 ft	28° / 100 ft	20° / 100 ft



WE OFFER

MWD / LWD Drilling Services with MWD specialists

MWD / LWD Kit Rental daily / monthly

MWD / LWD Kit Sales – customize your kit depending on your needs

Part Sales

MWD / LWD shop setups

MWD / LWD training

SERVICES

In-house Repairs & Tool Servicing

In-house Subs Repairs & Coating

In-house Engineering Technology Development

